

Superwhite 34 Blown Insulation - Cavity Wall

Typical application: New-build external masonry cavity walls



Description

Superglass Superwhite 34 is a high performance, non-combustible and British Board of Agrément (BBA) approved glass mineral wool blown cavity wall insulation. Superwhite 34 has a 10 year guarantee.

Application

Superglass Superwhite 34 is designed to provide thermal insulation for new build masonry cavity walls with a minimum cavity width of 90mm and up to 12m in height. It can be installed in buildings of 12m – 25m in height subject to a satisfactory inspection of the wall construction and installation approval by Superglass Insulation. Superwhite 34 is BBA approved for all UK exposure zones (subject to conditions detailed in the BBA Certificate and NHBC Standards).

Superwhite 34 may also be used in party walls and is a component in a number of Robust Details Solutions including proprietary system E-WM-33.

Installation

Superglass Superwhite 34 is installed after the walls are built, from inside the building. It's installed quickly and easily in any weather using existing machinery by a national network of Superglass and BBA approved contractors.



BRE Green Guide Rating

Superwhite 34 has a generic BRE Green Guide Rating of A+.



Fire Performance

Superwhite 34 has a fire classification of A1 (the highest possible rating) when tested to BS EN 13501-1 Reaction to Fire.



Thermal Insulation

Superwhite 34 has a thermal conductivity of 0.034W/mK.



Recycled Content

Superwhite 34 is manufactured from up to 84% recycled glass.



Efficient Installation

Installation is quick and easy in any weather by our network of Superglass & BBA approved contractors.



Superwhite 34 | Characteristics

For an installed density of 25kg/m³ the following coverage should be obtained per bale.

Cavity Width (mm)									
90	100	110	115	125	135	145	150	155	165
Coverage (m ² /bale**)									
7.30	6.60	6.00	5.80	5.30	4.90	4.60	4.40	4.30	4.00

** Coverage calculation rounded to nearest 0.1m²/bale.

28 packs per pallet.
Nominal weight per bale = 16.60kg
Product Code = 1030A

Thermal Performance

Superwhite 34 has a declared thermal conductivity of 0.034W/mK when tested to BS EN 14064-1: 2010 (Lambda 90/90).

Fire Performance

All Superglass products are deemed non-combustible and have a fire classification of A1 (the highest possible rating) when tested to BS EN 13501-1 Reaction to Fire.

Environment

- Manufactured in accordance with ISO 14001 - Environmental Management Systems (EMS).
- Contains no ozone-depleting substances or greenhouse gases.
- Generic BRE Green Guide Rating of A+.
- A copy of the Environmental Product Declaration (EPD) can be downloaded from the Superglass website.

Recycled Content

All Superglass products are manufactured from up to 84% recycled glass which would otherwise go to landfill.

Standards

Manufactured in accordance with:

- BS EN 14064-1: 2010 for In-situ formed loose-fill mineral wool products
- BS EN 13172 Thermal insulation products - Evaluation of conformity.

Quality

All Superglass products are manufactured in accordance with BS EN ISO 9001 - Quality Management Systems (QMS).

Cavity Width (mm)									
90	100	110	115	125	135	145	150	155	165
R-Value (m ² K/W)									
2.60	2.90	3.20	3.35	3.65	3.95	4.25	4.40	4.55	4.85

Durability

All Superglass products are non-hygroscopic, will not rot, degrade or sustain vermin and will not encourage the growth of mould, bacteria or fungi.

Water Resistance

When the product is properly installed in accordance with BBA Certificate 14/5086 Product Sheet 2, it will resist any water transfer across the cavity to the inner leaf.

Vapour Resistance

All Superglass products offer negligible vapour resistance allowing vapour to pass freely through the insulation.

Handling & Storage

All Superglass products are easy to handle, cut and install. The products are supplied compression packed in polythene to provide short term protection only. For long term protection, the product must be stored indoors, or under a waterproof covering and off the ground to protect from weather damage. The products should not be left permanently exposed to the elements.

Certification

- UKCA certified to BS EN 14064-1: 2010.
- A copy of the Superwhite 34 Declaration of Performance (DoP) ref: UKCA0016 can be downloaded from the Superglass website.

Guarantee

Superwhite 34 has a 10 year guarantee.

Associated Products

Superwhite 34 - Party Wall



Superglass Insulation Limited. Thistle Industrial Estate, Kerse Road, Stirling, Scotland FK7 7QQ

Technical

Hotline: **0808 1645 134**

Email: **technical@superglass.co.uk**

Customer Service

Tel: **01786 451170**

Email: **customerservice@superglass.co.uk**

Social

www.twitter.com/Superglass_UK

www.linkedin.com/company/superglassuk/

All rights are reserved, including those of photomechanical reproduction and storage in electronic media. Commercial use of the processes and work activities presented in this document is not permitted. Extreme caution was observed when putting together the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of errors pointed out.

